



ECO PLUS
POWER SUPPLY

SPECIAL FEATURES

- ❖ 80 PLUS® Bronze Certified High Efficiency
- ❖ Highly Reliable 105 °C Japanese Brand Capacitor
- ❖ Ample +12 V Outputs
- ❖ Active Power Factor Correction (99 % PF Typical)
- ❖ Double Forward Converter Design
- ❖ Smart and Silent Fan Control (S²FC)
- ❖ 120 mm Cooling Fan
- ❖ Soft-Mount Rubber Cushions
- ❖ Patented Easy Swap Connector
- ❖ Universal AC Input (Full Range)
- ❖ Ultra Ventilation (Honeycomb Structure)
- ❖ 3 Years Warranty



POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
ECO PLUS 600	24 A	24 A	46 A	0.8 A	2.5 A	600 W
	130 W		552 W	9.6 W	12.5 W	
ECO PLUS 500	24 A	24 A	34 A	0.8 A	2.5 A	500 W
	130 W		408 W	9.6 W	12.5 W	
ECO PLUS 400	20 A	20 A	30 A	0.8 A	2.5 A	400 W
	130 W		360 W	9.6 W	12.5 W	

WIRE CONFIGURATION

Model	Cable					
	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
ECO PLUS 600	1	1	2	8	2	1
ECO PLUS 500	1	1	2	5	2	1
ECO PLUS 400	1	1	2	4	2	1



Safety & EMI / EMC   **CB** **CE**   

Protection Features: OPP, OVP, SCP, UVP

Dimensions: 150 mm (L) x 140 mm (W) x 86 mm (H)



Specifications may change without prior notice



Headquarters sales@seasonic.com

USA ssa.sales@seasonic.com

Europe sse.sales@seasonic.com

www.seasonic.com